MATERIAL SAFETY DATA SHEET

This MSDS conforms with General Administrative Regulations of 6 Sept.1996 (ISO-11014/ANSIZ400.1.1996)

This header should be replaced with a company identication/letter header giving postal address and Telephone number(s) with the same dimensions.

Name : DURA-FLEX QUICKFIX POTHOLE FILLER Code : 95.10.0A Date Issued : 10/3/05



SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION

 Name : DURA-FLEX QUICKFIX POTHOLE FILLER
 Code : 95.10.0A
 Date Issued : 10/3/05

 EC Label : Not applicable
 EcoChem : 95.10.0A
 UN No. : N/A
 EAC : 127
 Hazchem : 3[Y]
 Kemler : 33
 SAPMA : 3-H-E

 In emergency contact As given above () at
 SAPMA : 3-H-E
 SAPMA : 3-H-E
 SAPMA : 3-H-E

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

EC Classification : Not classified as hazardous

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS HIGH BOILING ALIPHATIC >10 % [CAS #:] [E.C. #: o] EEC Labels : OEL 757mg OEL 100ppm STOEL 720mg STOEL 125ppm RL

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

SECTION 3. HAZARDS IDENTIFICATION

SAPMA Health Rating : 3-SLIGHT - Irritation or minor reversible injury possible Inhalation : Irritating, narcotic. Skin : Irritating, risk of dermatitis. Eyes : Irritating. Ingestion : IRRITATING No carcinogenic, mutagenic or genetic effects established May have short-term environmental effects. Contain, monitor & remove.

SECTION 4. FIRST AID MEASURES

Inhalation : Move to fresh air. In case of discomfort seek medical attention. Skin : Use hand cleaner/soap & water. Remove contaminated clothing. If any discomfort get medical attention Eyes : Rinse immediately with plenty of water. Seek medical advice if symptoms persist. Ingestion : DO NOT INDUCE VOMITING. Get immediate medical attention.

SECTION 5. FIRE FIGHTING MEASURES

Combustible with toxic fumes. Containers can burst in a fire. Can form explosive vapour/air mixture. Static discharge hazard! Foam. CO2. Dry powder. Fog to cool and control. Do NOT use water jets. Cool containers in case of fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5, 8, 13

Contain & collect. Use an inert - NOT sawdust. Keep out of drains & sewers.

SECTION 7. HANDLING AND STORAGE

Store separately from any reactive substances - oxidisers in particular. No open flames. No smoking. Keep containers cool. Avoid free fall of liquid - use earthing. Subject to local bylaws

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

SAPMA Rating : 3-H-E PPE : Respirator and Eye protection Inhalation : In case of insufficient ventilation, use suitable respiratory protection. Skin : Use barrier cream and impervious gloves. Eyes : Use face shield & goggles or full face respirator/hood. Avoid direct contact. Ingestion : Observe the rules of hygiene. Wash before eating or drinking. OEL Type : Mixture- Mixture - See Section 2



SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions Could generate static - USE EARTHING Inert - no reaction with fire-fighting water

SECTION 11. TOXICOLOGICAL INFORMATION

No carcinogenic, mutagenic or genetic effects established Toxicity levels not established

SECTION 12. ECOLOGICAL INFORMATION

May have short-term environmental effects. Contain, monitor & remove.

SECTION 13. DISPOSAL INFORMATION

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.

SECTION 14. TRANSPORT INFORMATION

Not classified as dangerous for transport EAC : 127 Hazchem : 3[Y] Kemler : 33



SECTION 15. REGULATORY INFORMATION

EC Label : Not applicable EC Classification : Not classified as hazardous

- S2 Keep out of reach of children. (Retail sales items)
- S23- Do not breathe fumes, vapour or spray.

S24 - Avoid contact with the skin

S43 - In case of fire, use water fog, foam or powder - Do not use water jets!

S62 - If swallowed, do not induce vomiting : seek medical advice immediately and show this container or label.

SECTION 16. OTHER INFORMATION

TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES. IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

> This MSDS conforms with General Administrative Regulations of 6 Sept.1996 (ISO-11014/ANSIZ400.1.1996) OELs derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42) SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991) All information is given in good faith but without guarantee in respect of accuracy. No responsibility is accepted for errors or omissions or the consequences thereof.

> > (Date of issue : 10/3/05 Generic last modified : 7/4/99 Specific last modified : 10/3/05)