MATERIAL SAFETY DATA SHEET

This MSDS conforms with General Administrative Regulations of 6 Sept.1996 (ISO-11014/ANSIZ400.1.1996)

This header should be replaced with a company identication/letter header giving postal address and Telephone number(s) with the same dimensions.

Name: DURA-FLEX QUICKFIX POTHOLE FILLER Code: 95.10.0A Date Issued: 10/3/05



SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION

Name: DURA-FLEX QUICKFIX POTHOLE FILLER Code: 95.10.0A Date Issued: 10/3/05

In emergency contact As given above () at

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

EC Classification: Not classified as hazardous

HAZARDOUS AND/OR OTHER RELEVANT COMPONENTS

HIGH BOILING ALIPHATIC >10 %

[CAS #:] [E.C. #: o]

EEC Labels: OEL 757mg OEL 100ppm STOEL 720mg STOEL 125ppm RL

(CL/RL = Controlled/Recommended level 'S' = Skin annotation)

SECTION 3. HAZARDS IDENTIFICATION

SAPMA Health Rating: 3-SLIGHT - Irritation or minor reversible injury possible

Inhalation: Irritating, narcotic. Skin: Irritating, risk of dermatitis.

Eyes : Irritating.

Ingestion: IRRITATING

No carcinogenic, mutagenic or genetic effects established

May have short-term environmental effects. Contain, monitor & remove.

SECTION 4. FIRST AID MEASURES

Inhalation: Move to fresh air. In case of discomfort seek medical attention.

Skin: Use hand cleaner/soap & water. Remove contaminated clothing. If any discomfort get medical attention

Eyes: Rinse immediately with plenty of water. Seek medical advice if symptoms persist.

Ingestion: DO NOT INDUCE VOMITING. Get immediate medical attention.

SECTION 5. FIRE FIGHTING MEASURES

Combustible with toxic fumes.

Containers can burst in a fire. Can form explosive vapour/air mixture. Static discharge hazard!

Foam. CO2. Dry powder. Fog to cool and control. Do NOT use water jets.

Cool containers in case of fire.

SECTION 6. ACCIDENTAL RELEASE MEASURES - SEE ALSO SECTIONS 5, 8, 13

Contain & collect. Use an inert - NOT sawdust. Keep out of drains & sewers.

SECTION 7. HANDLING AND STORAGE

Store separately from any reactive substances - oxidisers in particular.

No open flames. No smoking.

Keep containers cool. Avoid free fall of liquid - use earthing.

Subject to local bylaws

MSDS: Name: DURA-FLEX QUICKFIX POTHOLE FILLER Code: 95.10.0A Date Issued: 10/3/05

Page 2 of 2

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

SAPMA Rating: 3-H-E PPE: Respirator and Eye protection

Inhalation: In case of insufficient ventilation, use suitable respiratory protection.

Skin: Use barrier cream and impervious gloves.

Eyes: Use face shield & goggles or full face respirator/hood. Avoid direct contact.

Ingestion: Observe the rules of hygiene. Wash before eating or drinking.

OEL Type: Mixture - See Section 2









SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

FlashPoint (°C): >63 Insoluble in water

SECTION 10. STABILITY AND REACTIVITY

Stable under normal conditions Could generate static - USE EARTHING Inert - no reaction with fire-fighting water

SECTION 11. TOXICOLOGICAL INFORMATION

No carcinogenic, mutagenic or genetic effects established Toxicity levels not established

SECTION 12. ECOLOGICAL INFORMATION

May have short-term environmental effects. Contain, monitor & remove.

SECTION 13. DISPOSAL INFORMATION

Use reputable waste disposal contractors. Exercise caution in disposal of used containers.

SECTION 14. TRANSPORT INFORMATION

Not classified as dangerous for transport EAC: 127 Hazchem: 3[Y] Kemler: 33





SECTION 15. REGULATORY INFORMATION

EC Label : Not applicable

EC Classification: Not classified as hazardous

S2 - Keep out of reach of children. (Retail sales items)

S23- Do not breathe fumes, vapour or spray.

S24 - Avoid contact with the skin

S43 - In case of fire, use water fog, foam or powder - Do not use water jets!

S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

SECTION 16. OTHER INFORMATION

TAKE PRECAUTIONARY MEASURES AGAINST STATIC DISCHARGES. IN CASE OF ANY DISCOMFORT ALWAYS SEEK MEDICAL ADVICE.

This MSDS conforms with General Administrative Regulations of 6 Sept.1996 (ISO-11014/ANSIZ400.1.1996)
OELs derived from OHS Act Regulations for Dangerous Chemical Substances of 25 Aug.1995 (EH-42)
SAPMA Rating - South African Paint Manufacturers Association Guide to Health Hazards (SABS ARP 006:1991)
All information is given in good faith but without guarantee in respect of accuracy.
No responsibility is accepted for errors or omissions or the consequences thereof.

(Date of issue: 10/3/05 Generic last modified: 7/4/99 Specific last modified: 10/3/05)